



Type 2

EV Meter Pay

A smart level-2 public charging station designed for hotels, shopping centers, parking lots, workplaces, municipalities and more.

This universal charging station is equipped with a built-in card reader that accepts every payment method including debit and credit cards, digital wallets, QR codes, prepaid, NFC and more. EV Meter's smart, secure and feature-rich solution enables businesses to take initiative and maximize their revenue.



24/7 Monitoring

Real-time event notifications and remote software updates



Easy Installation

Quick to deploy in any location



Weather Resistant

Designed to withstand any environmental conditions



Open Payment System

Accept any type of payment method



OCPP Supported

Manage the charging station by using EV Meter Core or any other management platform



Multi-Language

Operates in 15 languages with unique voice interaction features



EV Meter Pay



| | | |
|---|---|---|
| Electrical Data | AC Power Supply AC Input Voltage AC Output Voltage Maximum Input / Output Current Maximum Input / Output Power Number of Plugs | 3P + N + PE 380-400 VAC +/-10%, 50-60Hz 380-400 VAC +/-10%, 50-60Hz 3x32A 22kW One |
| Communication | Interface Protocol Server Communication | OCPP 1.6 Supported Ethernet, 4G |
| Supported Payment Schemes | Debit & Credit Cards Mobile & NFC Payments Prepaid cards & closed environments Static and Dynamic QR codes | Swipe, contact, contactless, EMV chip cards Google Pay, Apple Pay, Swish and more Alipay, WeChat Pay and others |
| Safety & Protections | Safety Protections Power Limit Control Type 2 Socket Protection Available Connections | Electronic RCD 30mA AC Electronic 6mA DC Fault current detection Mode 3 PWM control according to IEC 61851-1 IEC 62196-1, IEC 62196-2 Type 2 Socket or 5m Cable with Plug |
| Enclosure & Environmental Conditions | IP Rating Enclosure Material Operating Temperature Ambient Temperature Storage Status LEDs Light Beacon Built-in Energy Meter | IP55 PC + UV (-25°C) to (+55°C) (-30°C) to (+70°C) Yes RGB color indicator Yes |
| Weight & Dimensions (WxHxD) | Cable Socket | 450x300x180 mm, 8Kg 480x300x180 mm, 6Kg |
| Standards & Certifications | ROHS REACH CE Compliant | |
| Optional Devices | Type 2 Socket Protection Dynamic Load Management Pedestal | Shutter Yes Yes |