

TESIDA

Tethered Wall Box

22kW 32A



5M
TETHERED LEAD



TYPE 2
Connector



IP54 RATED
Waterproof



IK10
Impact protection



Part No.	Description
TSDACCG006A-22-4G	Tesida Tethered (Type 2) 22KW/32A (4G)
TSDACCG006A-22-RFID-4G	Tesida Tethered (Type 2) 22KW/32A + RFID (4G)
TSDACCG006ALM-22-4G	Tesida Tethered (Type 2) 22KW/32A + Load Management (4G)
TSDACCG006ALM-22-RFID-4G	Tesida Tethered (Type 2) 22KW/32A + Load Management + RFID (4G)

Datasheet		22kW Tethered
Input	Power Supply	3P+N+PE
	Rated Voltage	380V AC
	Rated Current	32A
	Frequency	50Hz/60Hz
Output	Output Voltage	380V AC
	Maximum Current	32A
	Rated Power	22kW
Use Appearance	Charge Connector	Type 2 cable
	Cable Length	5 Meter
	Enclosure	Steel
	LCD Display	4.3" screen
	Start Mode	Play/RFID card/APP control
Safety	Emergency Stop	Yes
	Ingress Protection	IP65
	Impact Protection	IK10
	Leakage Protection	TypeA+DC6ma
	Ground Protection	PEN Fault
	Electrical Protection	Over current protection, Residual current protection, Surge protection, Over/Under voltage protection, Over/Under frequency protection, Over/ Under temperature protection
	Certification	CE
	Certification Standard	EN 61851-1: 2017, EN 61851-21-2: 2018
Warranty	3 years	
Environment	Installation	Wall-mount/Pole-mount
	Work Temperature	-30°C~+50°C
	Work Humidity	5%~95%
	Work Altitude	<2000m
Package	Product Dimension	350*245*110mm (H*W*D)
	Package Dimension	490*380*300mm (L*W*H)
	Net Weight	5kg
	Gross Weight	6kg
	External Package	Carton
Features	Load Management	Available
	Application	Monta App

