

TESIDA

Untethered Wall Box

7.4kW 16/32A



TYPE 2
Connector



IP65 RATED
Waterproof



IK10
Impact
protection



Part No.	Description
TSDACCCT201A-4G	Tesida Untethered 7.4kW/32A (4G)
TSDACCCT201A-RFID-4G	Tesida Untethered 7.4kW/32A + RFID (4G)
TSDACCCT201ALM-4G	Tesida Untethered 7.4kW/32A + Load Management (4G)
TSDACCCT201ALM-RFID-4G	Tesida Untethered 7.4kW/32A + Load Management + RFID (4G)

Datasheet		7.4kW Untethered
Input	Power Supply	1P+N+PE
	Rated Voltage	230V AC
	Rated Current	16/32A
	Frequency	50Hz±2Hz
Output	Output Voltage	230V AC
	Maximum Current	16/32A
	Rated Power	7.4kW
Use Appearance	Charge Connector	Type 2 cable
	Cable Length	None
	Enclosure	Steel
	LCD Display	4.3" screen, touchscreen programmable
	Start Mode	Plug & Play/RFID card/APP control
	Emergency Stop	Yes
Safety	Ingress Protection	IP65
	Impact Protection	IK10
	Leakage Protection	TypeA+DC6ma
	Ground Protection	PEN Fault
	Electrical Protection	Over current protection, Residual current protection, Surge protection, Over/Under voltage protection, Over/Under frequency protection, Over/ Under temperature protection
	Certification	CE
	Certification Standard	EN 61851-1: 2017, EN 61851-21-2: 2018
	Warranty	3 years
Environment	Installation	Wall-mount/Pole-mount
	Work Temperature	-30°C~+50°C
	Work Humidity	5%~95%
	Work Altitude	<2000m
Package	Product Dimension	361*261*114mm (H*W*D)
	Package Dimension	490*380*200mm (L*W*H)
	Net Weight	5kg
	Gross Weight	6kg
	External Package	Carton
Features	Load Management	Available
	Application	Monta App

