SP-MC60-SPD, SP-MC80-SPD, SP-MC100-SPD


Single-phase PEN Fault Protection with MCB, load curtailment, and Type 2 SPD

The SP-MCXX-SPD single-phase protection device offers a compliant, simple, single connection centre, for EV charge point installations. Allowing connection to the existing TN-C-S earthing facility without the use earth electrodes. Designed to facilitate compliance with BS:7671 2018,

Amendment 2: 2022 Regulation 722.411.4.1 (iv)

The SP-MCXX-SPD units come complete with a double pole MCB and Type 2 SPD, and has the additional functionality for load curtailment, in line with Regulation 722.311.20. Isolating the charge point from the supply once the household consumption rises above the pre-set limit, and automatically restores the power to the charge point when the load falls back within a satisfactory level.

Please note, the load curtailment limit can be set at either, 60A, 80A, or 100A and must be selected at the time of order.





Product Features and benefits


- Built in matt:e PEN Fault Protection
- NO EARTH ELECTRODES REQUIRED
- Helps reduce disruptive and costly groundworks
- Removes the risk of striking buried services
- Simple wire in wire out connection
- Over current protection
- For loads up to 7.4kW
- Type 2 SPD
- Load curtailment
- Standard 1 Year parts warranty

...Simplifying EV connection



SP-MC60-SPD, SP-MC80-SPD, SP-MC100-SPD

Single-phase PEN Fault Protection with MCB, load curtailment, and Type 2 SPD



| Description | Single-phase Voltage Monitoring and Protection Unit |
|--------------------------|--|
| Certification | UKCA, CE |
| Input Volts | Nominal input voltage single-phase 230V 50Hz |
| Max Load | 7,4kW |
| Terminal Capacity | In Out $L/N: 2.5mm^{2} - 25mm^{2} \qquad L/N \ 2.5mm^{2} - 10mm^{2}$ $E: 2.5mm^{2} - 16mm^{2} \qquad E: 2.5mm^{2} - 10mm^{2}$ |
| Dimensions (H x W x D) | 225mm x 275mm x 85mm |
| Weight | Approximately 5kG |
| Enclosure | Mild steel |
| Ingress Protection | IP2X |
| Warranty | The matt:e <i>SP</i> -MCXX- <i>SPD</i> is guaranteed for a period of 1 years from the date of purchase. This warranty is limited to the replacement of faulty components only. |

...Simplifying EV connection

