Michryd



SCVCN_{PRO}

Product Datasheet



DATASHEET V1.3 2024

NTRODUCTION

The VCHRGD Seven Pro is a premium 7.4kW charging solution designed for domestic, fleet-at-home, destination, and workplace applications. Delivering 32A of single-phase power, this charger combines reliable performance with user-friendly features to support the needs of everyday EV charging.

With built-in WiFi, RFID, and Bluetooth connectivity, the Seven Pro ensures smooth operation and effortless management. Enhanced safety is provided by PEN, UV/OV & temperature protection, while dynamic load management optimises power usage across your system. Backed by a 3-year warranty, it's a solution built to last.

Featuring a sophisticated two-tone matte and glossy black design, the Seven Pro offers a clean, modern aesthetic that complements any setting. Its innovative push-fit installation simplifies setup and ensures ease of maintenance for years to come.

Practical, efficient, and stylish, the VCHRGD Seven Pro redefines cost effective convenience in EV charging.



INTRODUCTION


PRODUCT FEATURES





KEY FEATURES





















SPECIFICATION

KEY SPECIFICATIONS

Electrical Characteristics

Charger Type	Mode 3 (IEC61851-1)
Nominal Supply	Single phase 230V, 50/60Hz
Charging Power	Up to 32A (7kW)
Over Current Protection	40A
Current rating	Adjustable (6A to 32A)
Standby Power Consumption	<2.5W
Earth Leakage Protection	AC 30mA + DC 6mA (2P Type A RCBO Required)

PEN Protection BS7671:722.411.4.1 Ident V

Supply Connection L, N + PE / CT1 + CT2

Connectivity

WiFi	(IEEE 802.11bgn) @ 2.4Ghz WPA-2
Connection security	Transport Layer Secure Encryption HTTPS
Bluetooth	2.4GHz
RFID	~ 120 -140kHz
4G Cellular *Optional*	~ 600 MHz -2.5 GHz

Mechanical Features


Connector	Type 2 IEC62196
Mounting	Wall or Pedestal ·
Dimension (mm)	300 (L) 180 (H) 90 (D)
Weight	3kg approx. (excl. charging cable) 4kg w/ cable
IP Class/IK Class	IP54 / IK10

Safety & Operational Ratings

Status	LED Indication, Mobile App (OCPP 1.6J)
Operating Ambient Temperature	-25°C to 50°C
Relative Humidity	5% -95%
Atmospheric Pressure	80kPA -110kPA
EMC Compliance	IEC61000-4
Integral Protection	Under & Over Voltage, Temperature & Current
	6mA DC Leakage, RCDD
	PEN Fault Detection

SPECIFICATION

CASING & DIMENSIONS



PACKAGING

INSIDE THE BOX

INTERNAL PACKAGING

INTERNAL PROTECTIVE PACKAGING
KEEP ME GUIDE, FIXINGS PACK, 2X RFID CARDS



CHARGEPOINT

7KW CHARGEPOINT W/ CABLE IF TETHERED



EXTERNAL PACKAGING

PROTECTIVE CARDBOARD MATTE FINISH ANTI-SCUFF SLEEVE, RIGID CARDBOARD CORE PACKAGING WITH INTERNAL PROTECTION



ALL PACKAGING MATERIALS ARE 100% RECYCLABLE AND SHOULD BE RESPONSBILY DISPOSED OF AFTER INSTALLATION



• FIXTURES

4 X WALL MOUNTING SCREWS 4 X WALL PLUGS 3 X FERRULES 1 X TORX+ DRILL BIT 5 X TORX+ BACK BOX SCREWS



• CT CLAMP

1 X CT CLAMP AS STANDARD 2ND CT CLAMP IF ORDERED EASTRON SPLIT CORE CT 120A RATED INPUT 40MA OUTPUT 0.5% ACCURACY



◆ KEEP ME GUIDE

COMMISSIONING & SET UP GUIDE TO BE LEFT WITH CUSTOMER INSTALLER PASSWORD, APP SET UP CREDENTIALS & QR CODES TO DOWNLOAD USER/INSTALL APPS



• RFID CARDS

2 X TAP & CHARGE RFID CARDS USED TO AUTHORISE CHARGING IN TANDEM WITH VCHRGD HOME APP, OR IN STANDALONE RFID MODE IF NO DATA CONNECTION

NOTE | IT IS IMPORTANT TO ENSURE THAT THE CUSTOMER REPAIRS THE KEEP ME GUIDE FOR HOME APP SIGN UP AND ONGOING SUPPORT PURPOSES.

Looking to learn a little more? Why not reach out...

01494 370525



sales@vchrgd.com



www.vchrgd.com



1A Eghams Court, SL8 5YS



SIMPLICITY | SUSTAINABILITY | SUPPORT