




Datasheet ValkPitched - Slate roof hook (twist)

- Technical specifications**
- Mounting system for pitched roofs with slate tiles by screw fixing on impregnated construction wood attached to the roof's battens or rafters.
 - Roof hooks available for horizontal and vertical profile mounting (portrait / landscape).
 - ValkPitched – Slate roof hook (747869)
 - ValkPitched – Slate roof hook twist (747870)
 - Roof hook made of stainless steel.
 - To be used in combination with Speedflash as a replacement for original slate pan for a watertight finish.

- Requirements**
- Speedflash**
- Speedflash (Base + Cap) (747775)
 - Speedflash mounting material (747776)
 - Speedflash shield (747779) (*one-off purchase to protect underlying slate tiles*)

- Technical specifications**
- Speedflash**
- Material polypropylene, with an addition of UV and temperature resistant material which ensures a minimum lifespan of 20 years.
 - UV resistant.
 - Flame retardant.
 - Does not become brittle during frost periods.

Article information

Material number	747869	747870
Description	ValkPitched - Slate roof hook - Speed	ValkPitched - Slate roof hook - Speed twist
GTIN code	08719632528692	08719632528708
Image		
Weight	0,390 Kg per pc	0,430 Kg per pc
No. of pcs per box	50 pcs	40 pcs
Material number	747775	747776
Description	Speedflash - Slate roof hook	Speedflash mounting material
GTIN code	08719632528715	08719632528722
Image		
Weight	0,246 Kg per pc	0,008 Kg per pc
No. of pcs per box	20 pcs	20 pcs

- Calculations**
- Projects using the slate roof hook can be calculated easily and according to regionally applicable standards using the [ValkPVplanner](#).

CONTACT DETAILS | DEVELOPER AND PRODUCER OF SOLAR MOUNTING SYSTEMS