

2400W 2240Wh

Portable Power Station

Datasheet



Model		P2400S
General	Capacity	2240Wh
	Cell chemistry	LiFePO ₄
	Single cell capacity	50Ah @3.2V/pcs
	Lifecycle	4000+ Cycles to 80% Capacity
	Indicator	APP / TFT Screen
	Storage temp.	-10°C - 45°C
	Operating temp.	-10°C - 40°C
	Material	ABS + PC/Metal
	Weight	25.8 ± 0.5kg
	Dimensions	409W x 299H x 310D mm
	Battery Management System	OVP, UVP, OCP, SCP, OTP, UTP, etc.
	Solar charge system	MPPT charge controller
Input	XT60 (solar)	2 x 500W max (PV voltage range: 12V-59V)
	AC	2000W max (220-240V @50Hz)
Output	AC	2400W stable / 4800W peak (220-240V @50Hz)
	USB-C #1	45W max
	USB-C #2	100W Max
	USB-A	18W max (5V-12V)
	DC 5525	120W max per output @12V/10A
	Car port	(120W total output)

Photonic Universe Ltd
VAT: GB 124 6724 21

Company number: 7722726

Registered in England and Wales

Registered office:
TMS House
Cray Avenue
Orpington BR5 3QB UK

Tel: +44 (0) 203 150 11 11
Fax: +44 (0) 203 150 12 12
Email: info@photonicuniverse.com
Web store: www.photonicuniverse.com